


**Port Connections:**  
 P & T: 1/2" BSPP  
 M1, MP, FB/MH: 1/4" BSPP  
 H & Z : Section View B-B

PARTS LIST					
ITEM	QTY	PART NUMBER	DESCRIPTION	SW1	SW2
6	1	MVE 4 A	Relief Valve (0-700 bar)	27mm ~ 80 Nm	Slottet / 13mm
5	1	W-PB11A-30AL	Pressure Reducing Valve (7-210 bar)	22mm 7/8" ~ 47 Nm	Int. hex 4mm / 14.3mm
3	1	W-PFA11A3D0340N-WN	Solenoid Directional Valve	22mm 7/8" ~ 47 Nm	
27	3	2-630	Plug 1/4" BSPP incl. seal	Int. hex 6mm ~ 30 Nm	
2	1	3-029	Manifold		
16	2	3-610	K.S.BU7 12,4x2x15,78x1,68 NBR90		
100	4	2D-614	Bolt M8x110 12,9 DIN 912	Int. hex 6mm ~ 38 Nm	
1	1	HC3-...-A-D	miniBOOSTER		

Material			Issue	Material Code No.
Changes		Date	Name	Finish
Former drawing No. M-HC3-012-FL-00		01-03-2021	L.H.	
Manifold changed from 3-028 to 3-029		01-03-2021	L.H.	Break all edges
				Hardening depth
				HV
Designer	Leif Hansen	Scale 1:2	M-HC3-012-FL55	
Approved by		Format A3	Intensifier System	
Date	23-12-2014		Assembly Drawing	Drawing No.: M-HC3-012-FL55-01



Confidential: Property of miniBOOSTER HYDRAULICS A/S Denmark  
 Not to be handed over to, copied or used by third party.